

Robust and powerful, pneumatic operated fiber blowing machine designed for single cables and for relining of multiple micro ducts. Configuration can be made for cable between 4 and 40 mm and duct dimensions between 10 and 63 mm. The unique Joystick controller and the agile motors securing a optimal control of the installation. With an anodized aluminum construction, the machine is lightweight but still very strong.





FIBER BLOWING MACHINE FOR CABLE 4-40 MM / DUCT 10-63 MM

- Pneumatic operation, double motors.
- Gentle operation with long contact surface on the cable.
- Display for speed, distance and pressure in duct.
- Max. speed 65 m/min (215 ft./min), max pushing force on cable 1800 N.
- Adjustable clamping force.
- Option of sub-ducting kit makes most configurations possible: 7x7/3.5 mm or 4x14/10 mm. The machine can be carried out in several small microducts and, for example, in a 40 mm tube simultaneously.
- Works with JetLogger
- Joystick Controller with forward and reverse function.

NEWS!

More power: Pushing force up to 1800 N **Double Claw Pipe holder** (accessories)

TECHNICAL DATA



Max pressure:

16 Bar



Pushing force:

up to 1800 N



Cable diameter:

4 - 40 mm

Duct diameter:

10 - 63 mm

US: 3/4"-1,0"-1,25"-1,5"-2,0"



Weight:

approx 22 kg



Air connection:1" Claw connector



WxHxD

700x300x310




















STD CONFIGURATION V3

- Transport case
- Extra fixtur
- 1 bottle Micro Duct Lube
- 1 bottle Duct Lube
- 1 bottle pneumatic oil
- Service kit

ACCESSORIES FOR V3

- Afterblower
- Floating kit
- 9-12 V adaptor. For replacing 9 V battery for digital display
- Duct air quick release valve
- Jetlogger
- Duct clamps
- Cabel guides
- Double Claw Pipe Holder